

Low Voltage Cable Support

J Hook with Spring Steel Beam Clamp



Material/Finish:

J Hook: 1.2 mm G60 galvanized steel

Beam Clamp: 0.8 mm C1065 steel, finish is black E-coating

Angle Bracket: 2.0 mm G60 galvanized steel

Application:


Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic.

Advantages:


Easy installation to beam flanges

Wire retainer avaliable for 1-5/16", 2", 4", and 6".

UL File NO: E534419







Catalog Number	В	С	D	ФА	Flange Thickness	Cable Capacity Cat 6/Cat 5e/Fiber Optic	Static Load(F)	Std. Pkg.
ZQJH12SSBC	79.3[3.12]	22.0 [0.87]	18.3 [0.72]	3/4"	3/4"	10/16/16	60LBS	50
ZQJH21SSBC	107.3 [4.22]	34.1 [1.34]	18.3 [0.72]	1-5/16"	1-5/16"	30/50/50	60LBS	50
ZQJH32SSBC	118.0 [4.65]	35.0 [1.38]	18.3 [0.72]	2"	2"	50/80/80	60LBS	50
ZQJH64SSBC	178.0 [7.01]	49.0 [1.93]	18.3 [0.72]	4"	4"	185/300/300	60LBS	25
ZQJH96SSBC	178.0 [7.01]	49.0 [1.93]	18.3 [0.72]	6"	6"	230/450/450	60LBS	25