

# Hammer on Flange Clip (Bottom Mount with Snap Close Clamp)

## •Application:

Snap-lock conduit hanger/edge clip hammer-on assemblies are used when EMT or Rigid conduits must be supported below a structural beam.

•Material: Spring steel



| Catalog Number | Conduit Size | Flange Thickness | STD.PKG. |
|----------------|--------------|------------------|----------|
| ZQ6M-M24       | 3/8"         | 1/8"-1/4"        | 50       |
| ZQ6M-M58       | 3/8"         | 5/16"-1/2"       | 50       |
| ZQ6M-M912      | 3/8"         | 9/16"-3/4"       | 50       |
| ZQ812M-M24     | 1/2"or 3/4"  | 1/8"-1/4"        | 50       |
| ZQ812M-M58     | 1/2"or 3/4"  | 5/16"-1/2"       | 50       |
| ZQ812M-M912    | 1/2"or 3/4"  | 9/16"-3/4"       | 50       |
| ZQ16M-M24      | 1"           | 1/8"-1/4"        | 50       |
| ZQ16M-M58      | 1"           | 5/16"-1/2"       | 50       |
| ZQ16M-M912     | 1"           | 9/16"-3/4"       | 50       |
| ZQ20M-M24      | 1-1/4"       | 1/8"-1/4"        | 50       |
| ZQ20M-M58      | 1-1/4"       | 5/16"-1/2"       | 50       |
| ZQ20M-M912     | 1-1/4"       | 9/16"-3/4"       | 50       |
| ZQ24M-M24      | 1-1/2"       | 1/8"-1/4"        | 50       |
| ZQ24M-M58      | 1-1/2"       | 5/16"-1/2"       | 50       |
| ZQ24M-M912     | 1-1/2"       | 9/16"-3/4"       | 50       |
| ZQ32M-M24      | 2"           | 1/8"-1/4"        | 50       |
| ZQ32M-M58      | 2"           | 5/16"-1/2"       | 50       |
| ZQ32M-M912     | 2"           | 9/16"-3/4"       | 50       |