

Hammer On Clamp (Side Mount with Closed Clamp)

•Application:

Snap-lock conduit hanger/edge clip hammer-on assemblies are used when EMT or Rigid conduits must be supported below a structural beam.

•Material: Spring steel



Catalog Number	Conduit Size	Flange Thickness	STD.PKG.
ZQ6M-HOK24	3/8"	1/8"-1/4"	50
ZQ6M-HOK58	3/8"	5/16"-1/2"	50
ZQ6M-HOK912	3/8"	9/16"-3/4"	50
ZQ812M-HOK24	1/2"or 3/4"	1/8"-1/4"	50
ZQ812M-HOK58	1/2"or 3/4"	5/16"-1/2"	50
ZQ812M-HOK912	1/2"or 3/4"	9/16"-3/4"	50
ZQ16M-HOK24	1"	1/8"-1/4"	50
ZQ16M-HOK58	1"	5/16"-1/2"	50
ZQ16M-HOK912	1"	9/16"-3/4"	50
ZQ20M-HOK24	1-1/4"	1/8"-1/4"	50
ZQ20M-HOK58	1-1/4"	5/16"-1/2"	50
ZQ20M-HOK912	1-1/4"	9/16"-3/4"	50
ZQ24M-HOK24	1-1/2"	1/8"-1/4"	50
ZQ24M-HOK58	1-1/2"	5/16"-1/2"	50
ZQ24M-HOK912	1-1/2"	9/16"-3/4"	50
ZQ32M-HOK24	2"	1/8"-1/4"	50
ZQ32M-HOK58	2"	5/16"-1/2"	50
ZQ32M-HOK912	2"	9/16"-3/4"	50